



Odorox[®] Slimline[™] Hydroxyl Generator Air & Surface Protection

Product Specifications



PORTABLE



WALL-MOUNTED

Slimline™ Purifier

The Slimline™ hydroxyl generating purifier is designed for smaller spaces where a portable or wall-mounted unit is sought. It is ideal for offices and schools, senior living, conference and waiting rooms, and other commercial applications that need to purify and deodorize indoor spaces.

The table below summarizes the minimum treatment area in the absence of ventilation, and the treatment area range under typical operating conditions: 3 air changes per hour, 90% recirculated air and 9-foot (2.7-m) ceilings. These guidelines should be adhered to for optimal performance and safety.

Operating Guideline

Minimum Area (if there is no air circulation)	240ft ² (22m ²)
Treatment Range	215 – 900ft ² (20 - 84m ²)

Specifications

Dimensions (LxWxD)	18" x 5.2" x 25" (457mm x 133mm x 635mm)
Weight	17.6lbs (7.9kg)
Voltage	120V @ 60Hz / 230V @ 50Hz
Power	170 Watts (Max)
Number of Optics	1
Noise Level	52.8dBA - 69.9dBA
Airflow*	180 CFM *Airflows were measured with new/clean units
Filter	Washable filter 5.0" x 12.5" x 0.25" (127mm x 317.5mm x 6.4mm)
Shipping Dimensions	21" x 9" x 29" (533mm x 229mm x 737mm)
Shipping Weight	21.6lbs (9.8kg)
Certification	UL 507, CSA C22.2 #113, CE, RoHS, REACH
Warranty	2 years covering defects in workmanship or materials, but excluding spare parts and consumables

Distributed by:



sales@pyure.com
1.877.735.3701
pyure.com



Copyright 2024, The Pyure Company.
Slimline™ is a trademark of The Pyure Company,
Boynton Beach, FL 33426 USA
Document# SLM01LS000