

## Pyure HRC06™ Air Curtain Hydroxyl Generator Air & Surface Protection

**Product Specifications** 





## **HRC06<sup>™</sup> Air Curtain**

The HRCO6™ air curtain is designed for large treatment areas and can modulate hydroxyl output to sanitize and deodorize. This wall-mounted unit can be used in gymnasiums, large commercial spaces, warehouses and industrial applications.

The table below summarizes the minimum treatment area in the absence of ventilation, and the treatment area range under typical operating conditions: 3 air changes per hour, 90% recirculated air and 9-foot (2.7m) ceilings. If the treated space contains high contamination or strong odors, the effective treatment area will be smaller than the range listed below. These guidelines should be adhered to for optimal performance and safety.

## **Operating Guideline**

Minimum Area (if there is no air circulation) 4,012ft² (373m²)

Treatment Range 3,400 - 6,500ft<sup>2</sup> (316 - 604m<sup>2</sup>)

## Specifications

Dimensions (LxWxD) 45" x 31" x 29" (1143mm x 787mm x 737mm)

Weight 141lbs (63.95kg)

Voltage 120V @ 60Hz / 230V @ 50Hz

Power 1,200 Watts (max)

Number of Optics 6

Fan Rating Max. 1,500ft<sup>3</sup>/min (2,548m<sup>3</sup>/h)

Airflow\* 1512 CFM, 4000FPM (max) with 36" nozzle \*Airflows were measured with new/clean units

Noise Level 60dBA @ 10 feet (3m) from the unit

Filter 2 washable filters 17.75" X 12" X 1" / 2 washable filters 17.75" X 14.75" X 1"

Shipping Dimensions 55" x 23" x 35" (1,397mm x 584mm x 889mm)

Shipping Weight 280lbs (127kg)

Certification Contact Pyure for specific certification requirements

Warranty 2 years covering defects in workmanship or materials, but excluding spare parts and

consumables

Installation Installation requires an electrician (hard-wired to meet local electrical code)

The Pyure HRC06™ does not meet California air cleaner regulation requirements; cannot be shipped to California.

Distributed by:



pyure.com

